



ASTERIX DASH Tablet



The DASH is a robust Tablet PC, designed to provide mobility in many vertical applications. The DASH is sealed against spill and dust, and is sunlight readable for outdoor applications. With Windows 7 preloaded, application developers will take less time to migrate or develop a mobile application. As a result, the DASH allows a quicker "go-to-market" product release, and a larger return on investment.

- WiFi 802.11 b/g/n and Bluetooth
- RFID reader built-in (NFC ready)
- Integrated magnetic stripe reader
- Integrated barcode imager
- Slim and light, only 2.65 lbs (1.7 kgs)
- Sealed against spill and dust
- Sunlight readable for outdoor applications
- Certified to MIL-STD-810G and IP54 NEVA 13

Specification

Model	DASH
Display Size	10.1-inch" LED Backlight Screen with 5-wire Resistive Touch
Display Resolution	1366 (W) x 768 (H) WXGA
Sunlighting Readable	Yes
CPU	Intel® Oak Trail™ Atom 1.5
Memory	2GB
Storage	32 GB SSD
Operation System	Window 7 Embedded
Communication	Wi-Fi 802.11 b/g/n and Bluetooth 2.1
RFID (NFC)	13.56 MHz ± 7 KHz, ISO/IEC 14443A/B, 15693, Mifare and NFC ready
Webcam	1.3 Mega-pixel, audio input (Front Bezel), 2 Mega-pixel, LED auxiliary light (Rear Bezel)
Audio	2 x Speakers (internal)
Sensor	Light Sensor
USB 2.0 Type A	2
Audio Ports	1 x Microphone, 1 x Headphone
Docking Connector	1
Control Buttons	Power, Lock, WiFi
Navigation Buttons	4+ Way with integrated Enter button
Function Buttons	5 (Programmable)
Barcode Trigger	2 buttons (Programmable)
LEDs	Power, Storage, WiFi
Dimension (W x H x D)	10.95 x 8.11 x 1.05 inches (277.8 x 206 x 26.5 mm)
Weight	2.65 lbs (1.2 kg)
Certification	CE, FCC, UL, VCCI, CCC; CE/FCC SAR
Water / Dust Resistance	IP54 equivalent
Drop	4-foot drop (MIL-STD-810G Method 516.6 Procedure IV)
Mechanical Shock	Operating: 40g, 12ms, Terminal Sawtooth Non-Operating: 40g, 12ms, Terminal Sawtooth
Temperature	Operating Temperature: 32° F to 104° F (0° C to 40° C) Storage Temperature: -4° F to 140° F (-20° C to 60° C)
Humidity	5-90% without condensation
Battery	Internal Smart Lithium Polymer Battery, 3800mAH
Docking/Charging Station	Optional (Ports: Ethernet, (4) USB, VGA, HDMI)
Power Adapter	AC 100V~240V, 50~60Hz. Input: 19 VDC @3.42A, 65W
Accessories	Docking/Charging station External battery GPS module Magnetic stripe reader Barcode imager (1D and 2D)




Hand strap
(included)



Docking/Charging
station



Magnetic
stripe reader



Barcode imager
(1D and 2D)



GPS module



All trademarks belong to their respective companies.
Specifications subject to change without notice



<http://www.pioneerpos.com/tablet>

info@pioneerpos.com

Tel: 888-468-9757